

Grade: GS-SP4

Manufacturer: Superior Graphite Co.

| PROPERTY | US VALUE | | METRIC VALUE | |
|------------------------------|-----------------------|-------------------------|-------------------------|-----------------------|
| Carrier | Water | | Water | |
| Color | Dark Grey | | Dark Grey | |
| Consistency | Medium to Thick | | Medium to Thick | |
| Viscosity | >1,500 | cps | | |
| Bulk Density | 9.3-10 | lb/gallon | 1.11-1.2 | g/cm ³ |
| Flash Point | 200° | °F | NaN | °C |
| Dry Time (tack-free) | 180-240 min @ 70°F | | 180-240 min @ 21.1°C | |
| Dry Time (complete) | 24 hrs @ 70°F | | 24 hrs @ 21.1°C | |
| Average Application Coverage | 250 | ft ² /gallon | 6.1 | m ² /liter |
| Effective Temperature Range | -75°-450° | °F | -59.4°-232.2° | °C |
| Application Temperature MIN | 50 | °F | 10 | °C |
| Application Temperature MAX | 100 | °F | 38 | °C |
| Suggested Dilution Ratio | Not Recommended | | Not Recommended | |
| Suggested Dilutant/Cleaner | None Recommended | | None Recommended | |
| Shelf Life | 24 | months | 24 months | |