

SAFETY DATA SHEET

Spectracarb Gas Diffusion Substrates

Section 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product Name: Spectracarb Carbon Fiber Paper Mixture
Chemical Formula:
Synonyms: GDL, Gas Diffusion Layer/Material 2050A
Part No.: - 0550, 0850, 1050, 1550
Manufacturer: Engineered Fibers Technology (EFT), LLC
Distributor: FuelCellsEtc
Address: 1902 Pinon Drive, Suite B
City, State, Zip: College Station, TX 77845
Emergency Phone # / Email: +1 (979) 635-4706 / info@fuelcellsetc.com
Person Responsible for Preparation: BMP EH&S
Preparation/Revision Date: 2/1/14
Applications: Fuel Cell Material

Section 2: COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT NAME | CAS NO. | CONTENTS | EPA RQ | TPQ |
|-----------------|-----------|----------|--------|-----|
| Carbon | 7440-44-0 | >99% | N/A | N/A |

Section 3: HAZARDS IDENTIFICATION

This product is not classified as hazardous under the current CHIP regulations

EMERGENCY OVERVIEW:

Black carbonized substrate with no odour
WARNING! Wear self-contained breathing apparatus when fighting fires in confined locations. In the event of fire, use water spray, alcohol resistant foam, dry chemical, or carbon dioxide (CO₂)

INHALATION: Inhalation of dust may occur during material handling operations. Breathing dust may cause mild respiratory irritation and/or difficulty in breathing.

INGESTION: No adverse effects expected. May cause mild irritation to the gastrointestinal tract.

SKIN: Not expected to be a health hazard due to skin exposure. May cause mild skin irritation and redness.

EYES: May cause eye mild irritation, including watering and redness.

CHRONIC EFFECTS: May cause skin irritation. Prolonged inhalation of excessive dust may produce pulmonary disorders.

CARCINOGENICITY: IARC: Not Listed NTP: Not Listed OSHA: Not Regulated

ROUTES OF ENTRY: Inhalation (breathing). Eye and skin contact.

MEDICAL INFORMATION: Medical conditions aggravated: Allergies, eczema, and skin conditions.

Section 4: FIRST AID MEASURES

| | |
|--------------------|--|
| INHALATION: | Move the exposed person to fresh air at. Provide fresh air, warmth and rest, preferably in a comfortable upright sitting position. Get medical attention if any discomfort continues. |
| INGESTION: | Give water to drink to dilute. If large amounts of dust are swallowed seek medical attention |
| SKIN: | Not expected to require first aid measures. Wash affected areas with large amounts of running water and soap, if available for at least 15 minutes. Remove contaminated clothing and shoes. Seek medical advice if irritation develops. Wash contaminated clothing and shoes before reuse. |
| EYES: | Immediately rinse eyes with running water. Remove any contact lenses and continue flushing with running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of the eyes and lids with water. Get medical attention if any discomfort continues. |

Section 5: FIRE FIGHTING MEASURES

| | | | |
|---|--|----------------|-----|
| FLASH POINT: | Not Determined | METHOD: | N/A |
| EXTINGUISHER MEDIA: | Fire can be extinguished using: water spray, fog, or mist; alcohol resistant foam, dry chemical, or carbon dioxide (CO ₂). | | |
| PROTECTIVE MEASURES IN CASE OF FIRE: | As in any fire, wear NIOSH approved, positive pressure, self-contained breathing apparatus, and full protective gear. | | |

Section 6: ACCIDENTAL RELEASE MEASURES

Based on the material's physical properties, accidental releases are not expected. Pick up material in such a manner that does not generate dust. Use PPE identified in Section 8 and review Fire Fighting Measures before proceeding with clean up. Warning! Material may absorb hazardous materials.

Section 7: HANDLING AND STORAGE

| | |
|-----------------------------|---|
| USAGE PRECAUTIONS: | Wear appropriate protective equipment (See Section 8). Wash thoroughly after handling material. |
| STORAGE PRECAUTIONS: | Store in a cool, dry ventilated area. Protect against physical damage. Keep away from moisture and oxidizers. |

Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:



Section 8 continued: EXPOSURE CONTROLS AND PERSONAL PROTECTION

AIRBORNE EXPOSURE LIMITS

OSHA Permissible Exposure Limits (PEL):

Carbon ó total particulate 15 mg/m³ (TWA), respirable fraction - 5 mg/m³ (TWA)

ACGIH Threshold Limit Value (TLV)

Graphite - (all forms except graphite fibers) ó 2 mg/m³ (TWA)

ENGINEERING CONTROLS:

Use engineering controls to minimize generation of airborne particulate during material handling and processing operations.

VENTILATION:

Provide adequate general and local exhaust ventilation to keep employee exposures below the airborne exposure limits. Local ventilation is preferred since it can control emissions at the source, preventing dispersion into the general work area.

RESPIRATORS:

In conditions where high concentrations of airborne material are present (inadequate ventilation), wear a respirator that has been selected by a technically qualified person for the specific work conditions. For emergencies, use a full-face positive pressure, supplied air respirator.

SKIN PROTECTION:

Wear rubber gloves (natural, latex) and clean body-covering clothing.

EYE PROTECTION:

Wear approved safety glasses or safety goggles.

PROTECTIVE CLOTHING:

Wear appropriate gloves and long sleeved clothing when working with this material.

HYGIENIC WORK PRACTICES:

Wash at the end of each work shift and before eating, smoking, or using the lavatory. Launder clothing separate from other clothing.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|--------------------------|--|------------------------|----------|
| APPEARANCE: | Thin black substrate | COLOR: | Black |
| ODOUR/TASTE: | Odourless | % VOLATILE: | 0% |
| SOLUBILITY: | Insoluble in water or organic Solvents | FLASH POINT: | N/A |
| SPECIFIC GRAVITY: | Not Determined | VAPOR PRESSURE: | N/A |
| BURNING RATE: | Not Determined | VAPOR DENSITY: | N/A |
| MELTING POINT: | 3,550C (6,422F) | BOILING POINT: | Sublimes |
| UEL: | N/A | LEL: | N/A |

Section 10: STABILITY AND REACTIVITY

STABILITY: Stable Under ordinary conditions of storage and use.

CONDITIONS TO AVOIS: Moisture and incompatibles.

INCOMPATIBLEIES: Strong Oxidizers such as ozone, chlorine, permanganate may result in rapid combustion. Avoid contact with strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Involvement in a fire causes electrically conductive airborne particulate, carbon monoxide, carbon dioxide.

Section 11: TOXICOLOGICAL INFORMATION

| Ingredient Identification | NTP Carcinogen | | IARC Category |
|------------------------------|----------------|-------------|------------------|
| | Known | Anticipated | |
| Carbon (7440-44-0) | No | No | None |

Section 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS: Not regulated as dangerous for the environment

Section 13: DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Processing, use, or contamination of this product may change the waste management options. Dispose of in accordance with federal, state, and local requirements (state and local disposal regulations may differ from federal disposal regulations).

Section 14: TRANSPORTATION INFORMATION

PROPER SHIPPING DESCRIPTION:

Not Regulated
U.S. DOT, UN/NA NO.: Not Regulated
CANADIAN TRANSPORT: Not Regulated
TDGR CLASS: Not Regulated
TDGR LABEL: Not Regulated

Section 15: REGULATORY INFORMATION

Federal State & International Regulations, Part 1

| | SARA 302 | | SARA 313 | |
|--------------------|----------|-----|----------|-----------|
| | RQ | TPQ | List | Chem Catg |
| Carbon (7440-44-0) | No | No | No | No |

Federal State & International Regulations, Part 2

| | CERCLA | RCRA 261.33 | TSCA 8(d), 12(b) |
|--------------------|--------|-------------|------------------|
| Carbon (7440-44-0) | No | No | No |

Chemical Inventory Status - Canada

| | DSL | NDSL |
|--------------------|-----|------|
| Carbon (7440-44-0) | Yes | No |

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR), and the MSDS contains all of the information required by the CPR.

Section 16: OTHER INFORMATION

HAZARDOUS MATERIALS INFORMATION SYSTEM RATINGS:

| | |
|--------------|---|
| HEALTH | 1 |
| FLAMMABILITY | 0 |
| REACTIVITY | 0 |

LABEL PRECAUTIONS: Avoid contact with eyes, skin, and clothing.
Avoid breathing dust.
Use with adequate ventilation.
Wash thoroughly after handling.

LABEL FIRST AID: If airborne dust is inhaled, remove to fresh air. Seek medical attention for any breathing difficulty.

DISCLAIMER:

.....
Engineered Fibers Technology provides the information contained herein in good faith, but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving this information must exercise their judgment in determining its appropriateness for a particular purpose. Engineered Fibers Technology makes no representations or warranties, either expressed or implied, including, without limitation, any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Engineered Fibers Technology will not be responsible for damages resulting from use of or reliance upon this information.
.....

PREPARED BY:

Engineered Fibers Technology, LLC